



Craft of the Month - October, 2008 **DOMINO LIDDED BOX**



Material List

- Amazing GOOP® Craft adhesive
 - (53) Dominos
 - 5" x 5" of Ultrasuede or sticky-back felt (optional)
- Other Supplies:**
- Transparent tape
 - Grease pencil



Directions

Note: Read these directions and the instructions on the opposite side completely before beginning this project. Always work on a level and protected surface. Wax paper works great to protect work area. Use photos as a guide. Amazing GOOP® Craft is waterproof when cured.

- Start by arranging dominos in squares of eight dominoes each. You will make four sides, one bottom and one lid (which will have five additional dominoes for handle and stabilizers).
- Apply GOOP to inside edges of dominoes in each square, then hand squeeze a row of four dominoes together for a tight fit. Continue gluing domino rows for all pieces. At this point you should have two rows of four dominoes for each of the five squares needed for the box. Wait 15 to 20 minutes and apply GOOP to the top edges of bottom rows to finish the squares. Let cure for two hours.
- Now you are ready to complete the box. Apply GOOP around the side edges of the bottom square. Position each side square to touch the bottom square, bringing in two sides 1/8" at top. At each top corner you will need to add a small amount of glue to secure box sides (here is

where you will use the transparent tape to secure the box sides during glue curing time). Let cure for two hours.

- Glue lid the same way as sides and bottom except place one domino in middle of square top. Let cure for two hours. Turn square over and mark with grease pencil placement of stabilizer dominoes. These dominoes sit inside the walls of the box so the lid does not slip off.
- Turn box over and glue Ultrasuede or felt on bottom. (Optional)
- Pieces will become secure overnight. For full adhesive cure and complete solvent evaporation, allow box to sit for at least three days before packaging as a gift.



Stabilizers



Craft ADHESIVE

INSTRUCTIONS

1. Surface should be clean, dry and free of dirt. For best results, roughen surface before use. Use GOOP in a well-ventilated area.
2. Puncture the seal in the neck of the tube using the pointer cap. Product can be used between 50°F (10°C) and 90°F (32°C). Dry time decreases when used between 70°F (21°C) and 90°F (32°C).
3. Always test a small area to ensure proper application techniques and dry time.
4. Apply GOOP directly to each surface to be bonded or repaired. Allow GOOP to partially cure, 2-10 minutes before bringing surfaces together.
5. Allow the repair to dry for 24 hours. Depending on the materials and temperature, maximum strength may not be reached for 48 to 72 hours.
6. To ensure easy cap removal, apply a thin coat of petroleum jelly to the threads of the tube before replacing the cap.
7. Clean uncured adhesive with acetone or naphtha, the adhesive will ball up and brush off. Cured material may be removed by cutting or scraping.
8. For further information, call (800) 767-4667.

Note: GOOP may damage finished surfaces. Avoid such contact until GOOP is completely dry. GOOP is not recommended for any items that come into contact with food, drinking water or animals. Do NOT dry-clean GOOP because dry cleaning solvent breaks down the cured adhesive. GOOP is not recommended for use on polystyrene, polyethylene or polypropylene plastics. Do not use GOOP for bonding Styrofoam™ or paper products.

COMMONLY ASKED QUESTIONS

What temperature range does GOOP withstand?

GOOP can be applied in temperatures ranging from 50°F to 90°F. When cured, GOOP can withstand temperatures between -40°F and 150°F.

How can uncured GOOP be cleaned up?

Small amounts of acetone or citrus-based solvents may be used. GOOP will ball up and brush off.

How can cured GOOP be removed?

Cured GOOP may be removed by cutting or scraping.

How long does GOOP take to dry?

A full cure takes 24 to 72 hours, depending on the surrounding environment. Cure time increases with lower temperatures and decreases with high temperatures.

How can dry time be decreased?

To speed drying time, apply heat using a hand-held hair dryer. Set dryer on low and do not hold directly on GOOP.

Can GOOP be dry-cleaned?

No. Dry-cleaning solvent breaks down GOOP. GOOP is washer/dryer safe.

Can GOOP be used on Styrofoam™ ?

No. GOOP is not recommended for use on any *polystyrene*, *polyethylene* or *polypropylene* plastics.

What materials will GOOP adhere to?

GOOP works on virtually any material, including glass, plastic, metal, leather, vinyl, rubber, neoprene, poly carbonate, brick, marble, ABS, PVC, copper, waterproof cloth, aluminum, brass, wood, linoleum, fiberglass, Naugahyde™, porcelain and ceramic.

CAUTION - Flammable, Vapor Harmful: Contains toluene and petroleum distillate. May cause dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful.

WARNING: This product contains a chemical known to the state of California to birth defects or other reproductive harm.

Keep away from heat and flame. Extinguish all sources of ignition during and until all vapors are gone. Prevent build-up of vapors by opening all window and doors to achieve cross ventilation.

Use only with adequate ventilation. To avoid breathing vapor, open all windows and doors to assure fresh air movement during application and drying. Close container after use. Avoid contact with eyes and skin. Wash thoroughly after handling.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water and get medical attention; for skin wash thoroughly with soap and water. If swallowed, do not induce vomiting, get medical attention.

KEEP OUT OF THE REACH OF CHILDREN.

LIMITED WARRANTY: The manufacturer will not accept liability for more than product replacement.
www.eclecticproducts.com Made in the U.S.A. by Eclectic Products, Inc. - - Pineville LA 71361 09/08