

# Create Your Own

**E-6000®**  
Craft Adhesive

## Shadow Box - Beach Scene Materials List


## Shadow Box

Designed by Michele Nored for Eclectic Products, Inc.

- |  |                                       |
|--|---------------------------------------|
| E-6000® Craft Adhesive with snip tip                 | (1) 5 x 7 or 8 x 10 Beach Scene Print |
| (2) 11 x 14 Natural Wood Frames (with flat surfaces) | (3) 2-4" Tall Drift Wood Pieces       |
| (1) 11 x 14 Ivory Beveled Mat for 8 x 10 print       | (3) Seashells                         |
| (1) 12 x 15 Sky Blue Mat (for frame backing)         | (1) Miniature Seagull                 |
|  | 8" Small Jute or Twine                |



1 - Shadow Box with Beach Scene Memorabilia.



2 - Run E-6000 down center of bottom frame back.



3 - Make sure memorabilia isn't deeper than frame.



4 - Run E-6000 along outer edge of the top of mat.



5 - Allow to dry for 24 to 72 hours @ 70°F.

### Directions

Note: Read these directions and the instructions on the opposite side completely before beginning this project.

1. **TOP FRAME:** Pull tabs. Remove cardboard backing and extra papers. Leave glass and add 11 x 14 beveled mat. Secure in place using tabs. Set aside.
2. **BOTTOM FRAME:** Pull tabs. Remove cardboard backing, extra papers and glass. Press tabs back in. Leave frame face down. Using applicator tip, run a small bead of E-6000 down center of back of bottom frame. (See picture 2.)
3. Align **TOP FRAME** to **BOTTOM FRAME** back to back. Press down firmly in corners and edges, making frames flush with each other. Wipe off excess E-6000 promptly. Set aside.
4. Apply E-6000 to back of print. Center print to top of 12 x 15 mat. Using a ruler as a guide, adjust print to absolute center. Position and attach memorabilia to print using E-6000. (Make sure memorabilia is not deeper than your new shadow box before securing to mat. See picture 3.)
5. Using applicator tip, run a small bead of E-6000 along outer edge of top of 12 x 15 mat. See picture 4. Place picture frames on top of mat. Press down firmly in corners and edges, making sure print and memorabilia is centered within frame and beveled mat. Remove excess E-6000 promptly. (To keep corners from separating, set a heavy box over frames and leave overnight.)

# E-6000®

## INDUSTRIAL STRENGTH CRAFT ADHESIVE

### INSTRUCTIONS

---

1. Please read all directions before using. E-6000® should be used in a well-ventilated area.
2. Surface should be clean, dry and free of dirt. For best results, roughen surface before use.
3. Puncture the seal in the neck of the tube using the pointer cap.
4. Test small area before full use.
5. Best when used between 70°F and 85°F.
6. Cure time increases with lower temperatures and decreases with higher temperatures.
7. For maximum strength, allow the bond to dry longer than 48 hours.
8. Keep threads at the neck of the tube free of E-6000® residue. To ensure easy cap removal, apply a thin coat of petroleum jelly to the threads of the tube before replacing the cap.
9. Clean uncured adhesive with small amounts of acetone or citrus-based solvents. Cured material may be removed by cutting or scraping.
10. Store unused E-6000® at room temperature in a dry area.
11. For further information, call (800) 767-4667.

**Always test a small area before full use on any project to ensure proper application technique and dry time.**

**Note:** E-6000® May damage finished surfaces. Avoid such contact until E-6000® is completely dry.

### COMMONLY ASKED QUESTIONS

---

#### **What temperature range does E-6000® withstand?**

E-6000® can be applied in temperatures ranging from 50°F to 90°F. When cured, E-6000® can withstand temperatures between -40°F and 150°F.

#### **How can uncured E-6000® be cleaned up?**

Small amounts of acetone or citrus-based solvents may be used. E-6000® will ball up and brush off.

#### **How can cured E-6000® be removed?**

Cured E-6000® may be removed by cutting or scraping.

#### **How long does E-6000® take to dry?**

A full cure takes 24 to 72 hours, depending on the surrounding environment. Cure time increases with lower temperatures and decreases with high temperatures.

#### **How can dry time be decreased?**

To speed drying time, apply heat using a hand-held hair dryer. Set dryer on low and do not hold directly on E-6000®.

#### **Can E-6000® be dry-cleaned?**

No. Dry-cleaning solvent breaks down E-6000®. E-6000® is washer/dryer safe.

#### **Can E-6000® be used on Styrofoam™ ?**

No. E-6000® is not recommended for use on any polystyrene, polyethylene or polypropylene plastics.

#### **What materials will E-6000® adhere to?**

E-6000® works on virtually any material, including glass, plastic, metal, leather, vinyl, rubber, neoprene, polycarbonate, brick, marble, ABS, PVC, copper, waterproof cloth, aluminum, brass, wood, linoleum, fiberglass, Naugahyde™, porcelain and ceramic.

#### **Is E-6000® safe for photographs?**

E-6000® is photograph-safe and acid-free after a full cure of 24 to 72 hours at 70°F.

**CAUTION:** Contains perchloroethylene. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful. **WARNING:** This product contains a chemical known to the state of California to cause cancer. Harmful if inhaled or swallowed. May cause dizziness, headache or nausea. Can cause skin and eye irritation. Exposure may cause damage to the kidneys or liver. Cancer agent based on experimental data.

Keep away from heat and flame. Contact with flame or hot surface may produce toxic gases.

**Use only with adequate ventilation.** To avoid breathing vapor, open all windows and doors to assure fresh air movement during application and drying. When using do not eat, drink, or smoke. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

**FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. If swallowed, do not induce vomiting; get medical assistance. In case of eye contact, immediately flush eye with plenty of water for at least 15 minutes. For further health information, contact a poison control center.

#### **KEEP OUT OF THE REACH OF CHILDREN.**

CONFORMS TO ASTM D-4236

**LIMITED WARRANTY:** The manufacturer will not accept liability for more than product replacement.

www.e-6000.com

Made in the U.S.A. by Eclectic Products, Inc. - - Pineville LA 71361

05/04