

# FAMOCRETE™

## INSTANT CONCRETE REPAIR

**NON-SHRINKING**



### Strong, Fast-Setting Adhesion

### Specifically Formulated to be Applied to Vertical Surfaces

FAMOCRETE™ Instant Concrete Repair is a rigid, sag-resistant polyurethane repair product for broken or spalled concrete.

FAMOCRETE is easy to apply and is supplied in a ready-to-use universal cartridge. FAMOCRETE is 100% solids and cures quickly, forming a strong bond to concrete.



### Industries and Applications

- Walls** – fill voids or patch defects
- Pillars** – repair damaged areas
- Sidewalks** – transitions or spalls
- Curbs** – broken or damaged areas
- Driveways** – easy to apply

**Fast-Setting / Trowelable / Sandable / Paintable / Waterproof**



**FAMOCRETE**  
INSTANT  
CONCRETE REPAIR

RÉPARATION INSTANTANÉE DU BÉTON  
REPARACIONES DE CONCRETO INSTANTANEAS

**NON-SAG FORMULA**

MATÉRIAU QUI NE S'AFFAÏSE PAS  
FÓRMULA RESISTENTE A LA FLEXIÓN

Fast Setting • Trowelable • Sandable  
Paintable • Waterproof • Non-Shrinking  
Driveways • Sidewalks  
Curbs • Floors • Pillars



Fills Defects in Horizontal  
& Vertical Applications

Gray / Gris / Gris

**WARNING / RISQUES / ADVERTENCIA**  
MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION  
POTENTIAL SKIN AND OR RESPIRATORY SENSITIZER  
See other Cautions on Inside Panel

PEUT ÊTRE IRRITANT POUR LES YEUX, LA PEAU ET LA GORGE  
PEUT CAUSER UNE RÉACTION ALLERGIQUE AU NIVEAU DE  
LA PEAU ET DES VOIES RESPIRATOIRES

PUEDA CAUSAR IRRITACION EN OJOS, PIEL Y VIAS  
RESPIRATORIAS. PUEDE ACTUAR COMO SENSIBILIZANTE EN  
LA PIEL Y/O VIAS RESPIRATORIAS.  
Consulte otras precauciones en el panel posterior.

800-767-4667 famowood.com/ficr.htm

ISO 9001:2008 Compliant Quality Management System

**ECLECTIC**  
IN THE HOME & ON THE JOB PRODUCTS  
eclecticproducts.com

MADE IN THE U.S.A.

# FAMOCRETE™

## INSTANT CONCRETE REPAIR

**NON-SHRINKING**



### FAMOCRETE™ Instant Concrete Repair Product Characteristics and Properties

CONCRETE ADHESION	500 psi (3.4 MPa), ASTM D 4541. 100% substrate.
APPLICATION TEMPERATURE	Optimal temperature range is 65 - 85 °F (18 - 29 °C). May be applied at temperatures outside of this range (35 - 100 °F / 2 - 38 °C).
FULL CURE TIME	24 hours after application. <b>NOTE:</b> Polyurethanes cure faster at warmer temperatures and slower at cooler temperatures. Large repairs cure faster than small repairs.
SOLIDS	100% solids; No solvents.
UV RESISTANCE	Polyurethane is not sensitive to UV degradation; however, certain colors may change slightly
SHORE HARDNESS	Shore A/D 92/50, ASTM D 2240 (after 24 hour cure at room temperature)
HEAT RESISTANCE	Cured resin has very good heat resistance. (250 °F / 121 °C).



**6.1 fl oz (180 mL) cartridge and 2 mix tubes**  
(Uses heavy duty cartridge gun. Not included with kit.)

**NOTE: Non-Structural Use** - Material will not impact structural rating or certification of any concrete repair.

### PRODUCT BENEFITS

VOC %	Less than 1% VOC. <b>Contains no solvents.</b>
NON-SAG	Can be applied onto flat, sloped, and/or vertical concrete.
NO SHRINKING	Strong adhesion to concrete with no shrinking. Can be used for small or large voids or spalls.
EXCELLENT WORKING PROPERTIES	Easy to sand, grind, and paint. Sandable and paintable after 1 hour.
WORKING TIME	Material can be troweled for up to 3 minutes at optimal application temperatures.
SET TIME	Approximately 5 minutes
QUALITY REPAIR	Offers superior filling & patching of defects.
COLOR	Gray
VISCOSITY	16,000 cps, ASTM D 4878
YIELD	180 mL = 14.4 linear ft at 1/4" (4.32m at 6.3mm)
ANCHORING	ASTM E 488

### FAMOCRETE™ Instant Concrete Repair Ordering Information

Individual Size	Sales Part	Item UPC	Case Barcode	Case Pack	Case Weight	Case Dimensions (H x W x D in inches)	Case Cube
6.1 fl oz (180 mL) (Color: Gray)	1026801-180	0 76818-26801 7	2 00 76818-26801 1	12	11.75 lbs.	12.38 x 8.25 x 8.38	.50 ft <sup>3</sup>

For more information on these products, please contact your sales representative or call 800-767-4667.  
©2009 Eclectic Products, Inc. reserves the right to change specifications without written notification.  
famowood.com/ficr.htm

**ECLECTIC**  
IN THE HOME & ON THE JOB PRODUCTS  
eclecticproducts.com