



Distributed by:
Eclectic Products, Inc.
Pineville, LA 71361

Made in the USA

800.767.4667 - Technical Services

www.eclecticproducts.com

www.amazinggoop.com

TECHNICAL DATA SHEET

**Amazing GOOP®
Anti-Skid Epoxy with Grit**

PRODUCT DESCRIPTION

Amazing GOOP® Anti-Skid Epoxy provides a hard, flat, textured finish that helps avoid slip and fall accident. It is friendly on bare feet, lead-free and chemical, gas and oil resistant. Anti-Skid Epoxy can be used indoors or outdoors, and is ideal for areas where water is present or slippery conditions exist. The convenient aerosol can is the perfect solution to coat smaller or irregularly shaped surfaces, and can be used on properly prepared wood, concrete, metal, fiberglass, tiles, porcelain and many more surfaces.

APPLICATIONS

All Purpose Anti-Skid Epoxy with Grit

Helps avoid slipping and offers firm footing on:

- Stairs / Walkways
- Porches / Decks
- Ladders / Play Equipment
- Boats / Trailers
- Ramps / Patios
- Pool Decks / Ladders / Steps / Diving Boards
- Marina Areas
- Basement and Garage Floors
- Handicapped Areas
- Forklifts / Loading Docks
- And Many More

Bath, Tub & Tile Anti-Skid Epoxy with Grit

Helps avoid slipping and offers firm footing on:

- Bathtubs
- Showers
- Hot Tub Steps
- Tile Floors
- Gyms & Spas - Shower Stalls / Locker Rooms
- Handicapped Areas
- Pool Area - Decks / Ladders / Steps / Diving Boards
- And Many More

PRODUCT CHARACTERISTICS and BENEFITS

Substrates	Properly prepared wood, concrete, metal, fiberglass, tiles, porcelain and many more
Ease of application	Aerosol spray
Size	Net Wt. 11.0 oz/ 312 g metal aerosol can
Application Temperature	50 to 90 °F / 10 to 32°C
Dry to Touch	10 to 20 minutes at 77 °F / 25 °C
Recoat	approximately 1 hour at 77 °F / 25 °C
Dries Hard	24 hours at 77 °F / 25 °C before subjecting to light foot traffic and 48 hours for heavy foot traffic
Permanent	Yes, can be removed by sanding
Water Resistant	Yes, unique epoxy coating (not recommended for garage floors or wood surfaces subjected to standing water, or to be submersed under water for extended periods of time)
CFCs (Chlorofluorocarbon)	Contains no CFCs or other substances which deplete the ozone layer.

TECHNICAL DATA SHEET

PHYSICAL PROPERTIES

Vehicle type	Epoxy
Colors	All Purpose: Clear, White and Black (Gray, Safety Yellow and Safety Orange available with minimum order quantities) Bath, Tub & Tile: Clear ONLY
Coverage	Up to 15 sq. ft. per can
Solid Weight %	23 to 26%
Solid Volume %	12 to 14%
Paint %	46 to 49% per can (varies by color)
Lead Free	Pigments contain no lead
VOC	80% - Slip Resistant Coating
MIR	2.45
Chemical Resistance	Excellent
Gas and Oil Resistant	Excellent
Storage	Store in dry area at ambient room temperature of 72 °F / 22 °C.
Shelf life	1 year (unused) from date of manufacturing

DIRECTIONS FOR USE and APPLICATION NOTES

Always test a small area before full use.

- Step 1** Surface should be dry, clean and free of oil, wax, dirt, loose paint and other contaminants. If necessary, remove all the old paint down to the original surface. Aluminum surfaces should be treated first before applying Amazing GOOP® Epoxy. Wood surfaces should be primed with an oil based primer. Test a small area for color compatibility and adhesion.
- Step 2** For best results, spray between 70 and 90 °F/21 and 32 °C. Applying Amazing GOOP® Epoxy below 50 °F/10 °C will cause the paint to spray or dry improperly.
- Step 3** Mix contents of can well by shaking for 2-3 minutes. Mixing ball will roll freely when properly mixed. Continue to shake can intermittently for 10 seconds during use.
- Step 4** Spray 12 to 15 inches away from surface in a sweeping motion during application.
- Step 5** IMPORTANT: Clean valve immediately after each use. Hold can upside down and spray until only clear gas comes out (3-5 seconds). If spray nozzle becomes clogged, pull off and clean in lacquer thinner.

For technical assistance, call 800.767.4667.

- Please read all directions before using. Use in well-ventilated area only.
- Best when used between 70 and 90 °F / 21 and 32 °C.
- Dry time decreases with higher temperatures and increases with lower temperatures.
- Clean overspray with paint or lacquer thinner.

Surface Preparation Instructions:

METAL: Metal surface should be free of grease, rust or loose particles before painting. Wipe down metal with a clean rag and metal etch cleaner or lacquer thinner. Do not use cleaners that leave a film or residue. Allow the metal surface to dry completely before coating.

WOOD: Clean wood surface thoroughly to remove all dirt, grease or other contaminants. Remove all loose debris using a power washer or high pressure hose. Sand where necessary to remove loose wood grains and splinters. Allow to dry completely before coating (could take 2-3 days depending on temperature without rain or dew). For newly treated wood – season for 60 days before coating.

TECHNICAL DATA SHEET

TILE: Wipe tile with clean cloth and cleaner. Do not use cleaners which leave a film or residue after cleaning. Allow to dry thoroughly. Paint a test spot on the tile. After 24 to 48 hours test for adhesion using clear industrial grade tape (package strapping tape is standard for this test). Press tape down evenly on coating and then remove. If no paint is on the tape, adhesion is good. If the paint comes off, you may need to scuff or sand the tile lightly to promote adhesion. Be sure to clean all dust off the tile resulting from sanding. If applying on a tile bath tube or shower it is important to allow at least 24 hours dry time before resuming normal use (showers and baths). Allow 48 plus hours if the product is going to be subject to prolonged periods of soaking in water or chemical cleaners.

PORCELAIN: Wipe porcelain with a clean cloth and cleaner. Do not use cleaners which leave a film or residue after cleaning. Allow to dry thoroughly. Paint a test spot on the porcelain. After 24 to 48 hours test for adhesion using clear tape (package strapping tape is standard for this test). Press tape down evenly on coating and then remove. If no paint is on the tape, adhesion is good. If the paint comes off, you may need to scuff or sand the porcelain lightly to promote adhesion. Be sure to clean all dust off the porcelain resulting from sanding. If applying on a porcelain bath tube or shower it is important to allow at least 24 hours dry time before resuming normal use (showers and baths). Allow 48 plus hours if the product is going to be subject to prolonged periods of soaking in water or chemical cleaners.

CONCRETE: Remove all loose debris using a power washer or high pressure hose. A concrete etch is recommended to remove all grease, dirt, or other contaminants. Rinse concrete thoroughly to remove the etch and allow to dry (often 1-2 days depending on temperature, rain, dew and humidity). For new pours, allow concrete to season before coating – approximately 60 days. Apply Anti-Skid epoxy directly to concrete. No primer is needed.

FIBERGLASS: Sand lightly to promote adhesion. Wash with soap and water or wipe with a clean white cloth and lacquer thinner (or another cleaner that does not leave a film or residue) to remove all sanding dust. Allow to dry thoroughly.

UNPAINTED ALUMINUM: Clean using an aluminum metal etch. Rinse with water and allow to dry thoroughly. Apply directly to aluminum. No primer is needed.

PAINTED ALUMINUM: clean the part with soap and water or another cleaner that will not leave a film or residue. Spray Amazing GOOP® Anti-Skid Epoxy on a small test area to be sure that it will not remove the old paint. If Amazing GOOP® Anti-Skid Epoxy does not remove the old paint, proceed with spraying your project. If Amazing GOOP® Anti-Skid Epoxy removes the paint; you will want to completely remove the old paint with lacquer thinner or by some abrasive such as sanding. Follow the UNPAINTED ALUMINUM process.

HAZARDS

This product contains an epoxy ester. Before working with this product, read and become familiar with information concerning hazards, proper use and handling. To request an MSDS, please send an Email to msds@eclecticproducts.com or call 800.333.9826.

LIMITED WARRANTY

The product is warranted against any defect in materials or workmanship under normal use and service for a period of 180 days after the date of purchase. The product is also warranted under any implied warranties provided under applicable state law, including, without limitation, the implied warranty of merchantability and the implied warranty of fitness for a particular purpose, for a period of 180 days after the date of purchase. This warranty covers only the original buyer of the product. For warranty service, the buyer should contact the store where the product was purchased, or write Eclectic Products, Inc. P.O. Box 4450, Pineville, LA 71360 or call 800.767.4667. This warranty gives you specific legal rights, and you also have other rights, which vary from state to state.